

## PROFIT TECHNOLOGY

LEAD THE CHANGE

WITH 2623R (6x2)



Valiala Dimanaia			
Vehicle Dimensions	5075	2422	
Wheel Base (mm)	5275	6100	
Cabin	Sleeper	Mid cabin	
Loading Span (ft/mm)	24/7300	31.6/9640	
Overall Length (mm)	9885	11880	
Overall Width (mm)	2490	2490	
Overall Height (mm) (CBC)	2930	2930	
Front Overhang (mm)	1485	1485	
Rear Overhang (mm)	2400	3600	
Ground Clearance (mm)	230	230	
Engine  Facine Medal	OM 006		
Engine Model	OM 926		
Maximum Power, kW	180 kW @ 2,200 r		
Maximum Torque, Nm		850 Nm @ 1,200 – 1,600 rpm	
No. of cylinders, cc Emission Std	6, 7200 Bharat Stage VI - OBD-2		
Transmission	Bharat Stage VI -	OBD-2	
Gear Box Model & Type	GSE SELID Mos	hanical Synchromoch Goars	
		G85, 6F+1R, Mechanical, Synchromesh Gears Single dry plate, Hydraulic Control	
Clutch Type Clutch Dia, Wear (mm)	395, 4		
Power Take Off	Auxiliary Fitment		
Axle	Auxiliary Fittiletit		
Front Axle	IF 7.0		
Rear Axle	IR440+; Single tyre lift axle		
Rear Axle Ratio	5.875		
Chassis Frame & Suspension	0.010		
Frame Section (D X W X T) mm	286 x 70 x 8		
Front Suspension		eaf Spring with 2 Hydraulic Shock Absorbers	
Rear Suspension	Semi-elliptic, Multi Spring		
Anti-roll Bar		Front: Standard fitment	
		lard fitment for tankers and longer wheelbase variants	
Brakes			
Service Brake	Pneumatic, Foot	Operated, Dual Line with ABS	
Parking Brake	Pneumatically Op	Pneumatically Operated Hand Control Valve	
Front Brake Size (mm) & Type	Ø 410 drum	Ø 410 drum	
Rear Brake Size (mm) & Type	Ø 410 drum		
Steering			
Steering Type	Hydraulic Power	Assisted	
Fuel & Electrical System			
Fuel Tank / Filling Capacity	380L/355L 200L/185L*	380L/ 355L	
Adblue Tank / Filling Capacity	60L / 51L		
Battery Capacity	120Ah		
Voltage	24V		
Performance			
Maximum Gradeability %	27.10%		
Maximum Geared Speed kmph	80 kmph, 60 kmpl	h*	
TCD	22.7m	23.6m	
Tyres			
Pattern & Size	Radial Tyres - 295	5/90R20 / Tubeless Tyres - 295/80R22.5	
Weight			
Gross Vehicle Weight - GVW  * For specific tanker variants only	25500 kgs		