

## PROFIT TECHNOLOGY

LEAD THE CHANGE

WITH 4828RT (10×4)



Pattern & Size

Gross Vehicle Weight - GVW

Weight

recinition specifications		4020KI
Vehicle Dimensions		
Wheel Base (mm)	6575	
Cabin	Sleeper Cabin	
Overall Length (mm)	9635	
Overall Width (mm)	2490	
Overall Height (mm) ( CBC)	2955	
Front Overhang (mm)	1485	
Rear Overhang (mm)	900	
Ground Clearance (mm)	170	
Engine		
Engine Model	OM926	
Maximum Power, kW	210kW @ 2200 rpm	
Maximum Torque, Nm	1100Nm @ 1200 -1600 rpm	
No. of Cylinders, cc	6, 7200	
Emission Standard	Bharat Stage VI - OBD-2	
Transmission		
Gear Box Model & Type	G131, 9F+1R, Mechanical, Synchromesh Gears	
Clutch Type	Single Plate, Dry Type	
Clutch Dia, Wear (mm)	430, 4.5	
Power Take Off	Gearbox PTO Spline - Standard	
Axle		
Front Axle	IF 7.0	
Rear Axle	IRT390-11; Dual tyre lift axle	
Rear Axle Ratio	4.778	
Chassis Frame & Suspension		
Frame Section (D X W X T) mm	284 × 70 × 8	
Front Suspension	Parabolic	
Rear Suspension	All new Parabolic Bogie Suspension	
Anti-roll Bar	Standard on front & second rear axle	
Brakes		
Service Brake	Pneumatic, Foot Operated, Dual Line with ABS	
Parking Brake	Pneumatically Operated Hand Control Valve	
Front Brake Size (mm) & Type	Ø 410 drum	
Rear Brake Size (mm) & Type	Ø 410 drum	
Steering		
Steering Type	Hydraulic Power Assisted	
Fuel & Electrical System		
Fuel Tank / Filling Capacity	330L / 310L	
Adblue Tank / Filling Capacity	60L / 51L	
Battery Capacity	120Ah	
Voltage	24V	
Performance		
Maximum Gradeability %	28,20%	
Maximum Geared Speed kmph	60 kmph	
TCD	24 m	
Tyres		
Dattarn & Cina	Padial Turas 205/00P00	

Radial Tyres - 295/90R20

47500 kgs